



### Main Features

- Suitable for Analog and Digital TV
- Adjacent Channel Combination
- Double Cross Coupling
- Temperature Compensated
- High Q Coax Technique
- 19" Rack Shelf

### Electrical Specifications

Electrical Specifications				
Frequency range		470-806MHz		
ADJUSTING DATA		DVB-T/T2	ATSC 1.0/3.0	ISDB-T
Insertion Loss		f(0)≤0.55dB	f(0)≤0.65dB	f(0)≤0.70dB
		f(0)±3.8MHz≤1.4dB	f(0)±2.7MHz≤0.9dB	f(0)±2.79MHz≤1.6dB
		f(0)±3.9MHz≤1.9dB	f(0)±2.93MHz≤1.2dB	
Attenuation		f(0)±4.2MHz≥4dB	f(0)±3.5MHz≥10dB	f(0)±3.15MHz≥7dB
		f(0)±6.MHz≥18dB	f(0)±6.MHz≥24dB	f(0)±4.5MHz≥18dB
		f(0)±12MHz≥40dB	f(0)±9MHz≥36dB	f(0)±9MHz≥38dB
Isolation	Adjacent Channel	≥32dB	≥32dB	≥32dB
	1 Guard Channel	≥45dB	≥45dB	≥45dB
	Minimum Spacing			
Return loss / VSWR		≤-25dB/1.12	≤-25dB/1.12	≤-25dB/1.12
Temperature Stability		< 1kHz/K		
Max Power Output		350W		
Impedance		50 Ω		

### Environmental Specifications

Operating Temperature Range	-10°C to +55°C
Max Operating Temperature (Body)	65°C
Relative humidity	5% - 95%
Barometric pressure	55 KPa -106KPa

[anywavecom.net](http://anywavecom.net)

300 Knightsbridge Parkway | Suite 150 | Lincolnshire | IL | 60069

Phone: +1 (847) 415 2258 Fax: +1 (847) 415 2112

# UHF 350W Balanced Combiner

# Product Specifications



CMB-B-2U-350-NF / 78 / 158

Part Number: 200224.01 / 200225.01 / 200226.01



## Mechanical Specifications

Connectors (Input / Output)	N female	200224.01
	7/8" EIA	200225.01
	1 5/8" EIA	200226.01
Weight	19kg	
Outer Dimension (mm)	290 * 241.5 * 584mm	
Packing	1 Piece per box	



[anywavecom.net](http://anywavecom.net)

300 Knightsbridge Parkway | Suite 150 | Lincolnshire | IL | 60069

Phone: +1 (847) 415 2258 Fax: +1 (847) 415 2112